Lockwing



Utility Gas Ball Valve • Full Port • Service Bypass • 125 PSIG



125-LWBP

Features

- Tamper Resistant Lockwing Cap
- 2 FKM O-Rings
- Full Port Design to Accommodate Industry Leading Stop Changers
- Lockwing Accommodates Standard Barrel Locks
- Maintenance Free Design
- Patented Security Shutter and Lockwing Tab
 US Patent No. 6,648,009
- 100% Leak Tested
- 100% Made in Italy
- Leakproof Stem Lifetime Warranty

Approvals .

- CSA Certified
 - ANSI B16.33 (125G)
- Meets or exceeds applicable part of DOT 192


Pressure Rating


- 125 PSIG
- Temp range: -40°F to 300°F
- MSS SP-110



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, and lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.







Material Specifications

No.	Part	Materials					
1	Body*	Brass - C37700					
2	End Connection*	Brass - C37700					
3	Ball	Chrome Plated Brass - C37700					
4	Seat (2)	PTFE G300					
5	Stem	Brass - C38500					
6	Packing	Buna-N					
7	Stem O-ring (2)	FKM					
8	Packing Gland	Brass - C38500					
9	Lockwing Cap*	Brass - C37700					
10	Screw	304 Stainless Steel					
11	Bypass Plug*	Brass - C38500					
12	Bypass Set Screw	Brass - C38500					
13	Bypass O-ring	Viton®					
14	Bypass Cap*	Brass - C38500					

^{*}Component may be AGA painted depending upon selection

Dimensions

Part No.	Size	Α	В	C	D	E
244-005B	1"	3.65	2.21	2.18	0.95	0.59

-