



Black Iron Steel Dielectric Union

FIP x FIP Connection, 250 PSI

DIELECTRIC UNION



FEATURES


- Prevents Accelerated Corrosion
- For Use on Black Pipe
- Suitable for Use in Gas or Water Applications
- Buna Seats: -20°F to 180°F

CERTIFICATIONS/APPROVALS

- ANSI B1.20.1
- ASSE 1079

PRESSURE/TEMPERATURE RATING

250 PSI



MATERIALS

No.	Part	Material
1	Body	Steel - Black Finish
2	Tail Piece	Steel - Black Finish
3	Union Nut	Steel - Black Finish
4	Dielectric Ring	Nylon 66
5	Gasket*	Buna-N

DIMENSIONS

Part No	Size	A	B
701-403	1/2" FIP x 1/2" FIP	2.14	1.61
701-404	3/4" FIP x 3/4" FIP	2.21	1.83
701-405	1" FIP x 1" FIP	2.54	2.58
701-406	1-1/4" FIP x 1-1/4" FIP	2.73	2.96
701-407	1-1/2" FIP x 1-1/2" FIP	2.73	3.75
701-408	2" FIP x 2" FIP	3.12	4.3

 WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.