





Lead Free Brass x Galvanized Steel Dielectric Union

Press x MIP Connection, 250 PSI

DIELECTRIC UNION



FEATURES

Dezincification Resistance Brass Alloy
Prevents Accelerated Corrosion
EPDM Gasket: -20°F to 180°F
Wetted Surfaces Contain Less than .25% Lead Content

CERTIFICATIONS/APPROVALS

Conforms to IAPMO PS117
Conforms to ANSI B1.20.1
IAPMO Certified
- NSF 61-8
- NSF 372
- Uniform Plumbing Code (cUPC)
• IAPMO/ANSI Z1157-2014
• NSF/ANSI 14-2014

PRESSURE/TEMPERATURE RATING

250 PSI

MATERIALS

No.	Part	Material
1	Female Fitting	Zinc-Plated Steel
2	Gasket	EPDM
3	Press Fitting	Brass C46500
4	Ring	Polyethylene
5	Nut	Zinc-Plated Steel
6	O-Ring	EPDM

DIMENSIONS

Part No	Size	A	B	C	D	E	F
701-803G	1/2"	3.36	1.57	0.55	1.15	0.71	0.81
701-804G	3/4"	3.7	1.81	0.75	1.26	0.93	0.87



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm.
For more information go to www.P65Warnings.ca.gov.