

Thread Sealant



High Temperature Nickel Anti-Seize Lubricant and Thread Sealant



Nickel Anti-Seize

Part No.	Size	Case Qty
400-503	8 oz can	12
400-504	16 oz can	12

Description

Jomar's Nickel Anti-Seize is a non-seizing, nickel based, lubricant and thread sealant. It may be used to prevent seizing, corrosion and galling where extreme temperature conditions exist. Contains a high percentage of micro-fine nickel flakes and is fortified with high quality rust and corrosion inhibitors. It is lead free, nontoxic, and will not harden in can.

Temperature and Pressure Ratings

Brushable to: 10°F (-12°C)

Temperature Range: 0°F to 2600°F (-17°C to 1427°C)

Pressure Ratings: Gas – 3000 PSI (211 kg/cm²)

Liquid – 10,000 PSI (703 kg/cm²)

Approvals



Meets Mil. Spec. MIL-A-907E

Directions

Do not dilute. Stir well before using. Clean mating surfaces. Brush onto mating surfaces. Make up joint and apply appropriate torque, if required. Keep container closed at all times when not in use to avoid contamination.



WARNING: This product can expose you to chemicals including nickel, which is known to the State of California to cause cancer, and nickel, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Recommended for use with:

- Air
- Acetylene
- Alkalis, Dilute
- Ammonia
- Brine
- Carbon Dioxide
- Chlorinated Water
- Freon (All)
- Inert Gases
- Natural Gas
- Nitrogen Gas
- Refrigeration Gases

- Soap, Liquid
- Steam Lines
- Sugar, Liquid
- Water (Hot or Cold)

NOT FOR USE ON OXYGEN SYSTEMS

Recommended for use on:

- All types of metal
- PVC/CPVC
- Nylon
- Polypropylene
- Blowers
- Bolts
- Catalytic Crackers
- Couplings
- Drill Collars
- Flanges
- Fuel Nozzles
- Gaskets
- Gas Burners
- Gear Reducers
- Manhole Studs
- Nuts
- Pipe Fittings
- Plugs
- Pumps
- Screws
- Tool Joints
- Turbine Studs
- Valves