



Balancing Valve | RecircSetter™

Thermostatic Balancing, Variable Set Point, Dual Isolation, Actuated Thermal Disinfection, 150 CWP

TB-150MG



FEATURES

- Dezincification Resistant Brass Alloy
- Variable Temperature Set Point with Protective Cap
- Modulates Flow to Maintain Constant Temperature in Recirculation Loop
- No Balancing Equipment Required
- Drywell with Temperature Gauge Included
- 1/2" NPT Temperature Port (Factory Plugged)
- Equipped with Dual Isolation Ball Valves
- Union Connection on Ball Valves
- Integrated Check Valve in Downstream Isolation Valve
- Actuated Thermal Disinfection for use with BMS
- 100% Made in Italy
- NSF 61 & NSF 372 Certified
- Wetted Surfaces Contain Less than .25% Lead Content
- Accessories Available

CERTIFICATIONS/APPROVALS


- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372
- Conforms to ANSI B1.20.1

PRESSURE/TEMPERATURE RATING

- Max Working Pressure: 232 psi
- Max Differential Pressure: 14.5 psi
- Max Working Temperature: 194°F
- Temperature Setting Range: 95°F - 140°F
- C_{vmin} : 0.26
- C_{vmax} : 2.06
- $C_{vdesign}$: 0.55 - 0.58
- $C_{vdisinf}$: 1.16


DIMENSIONS

Part No	D	L	L1	L2	H	I	P	PT
180-103MG-A-I	1/2"	11.5	5.75	5.75	6.06	1.81	3.82	4.49
180-104MG-A-I	3/4"	11.5	5.75	5.75	6.06	1.81	3.82	4.49



HAND WHEEL SETPOINT TEMPERATURE (°F)									
95°	100°	105°	110°	115°	120°	125°	130°	135°	140°
1	1.6	2.1	2.7	3.2	3.8	▼ 4.4	4.9	5.5	6

Material Specifications



MATERIALS

No.	Part	Material
1	Valve Body	LF DZR Brass C27453
2	Spring	Stainless Steel AISI 302
3	1/2" Plug	LF DZR Brass C27453
4	O-Ring	EPDM
5	Disinfection Cap	LF DZR Brass C27453
6	Piston	PSU
7	Stem	LF DZR Brass C27453
8	Stem Adapter	LF DZR Brass C27453
9	O-Ring	EPDM
10	O-Ring	EPDM
11	Cartridge Piston	Steel
12	Cartridge Cup	Brass C22000
13	Cartridge Guide	Brass C69300
14	Cartridge Sleeve	EPDM
15	End Connection FNPT	LF DZR Brass C27453
16	Axial Valve Body	LF DZR Brass C27453
17	Shut-Off Spring	Stainless Steel AISI 302
18	Shut-Off Stem	Stainless Steel AISI 304
19	Shut-Off Gasket	EPDM
20	Shut-Off Metal Plate	Brass C38500
21	O-Ring	EPDM
22	O-Ring	EPDM

MATERIALS FOR TB-150MG ISOLATION VALVE

No.	Part	Material
1	T-Handle	Aluminum
2	Screw	Steel-Geomet Plated
3	Stem	LF Brass C28500
4	O-Ring (2)	EPDM
5	End Connection	LF DZR Brass C27453
6	Seat (2)	PTFE G300
7	Ball	T.E.A. Coated Brass C28500
8	O-Ring	EPDM
9	Body	LF DZR Brass C27453
10	Packing	PTFE G300
11	Packing Gland	LF Brass C28500
12	Union Gasket	EPDM
13	Union Nut	LF DZR Brass C27453
14	Check O-Ring	EPDM
15	Check Body	GF Noryl
16	Spring	Stainless Steel AISI 301
17	Check Rod Plunger	GF Noryl

