Fractional





APPLICATIONS

- Food & beverage processing
- Pasteurization systems
- Pharmaceutical
- Medical

10 SERIES

- 3/4" clamp, dry gauge
- Ranges from 0 psig to 30 psig through 0 psig to 600 psig
- 2" gauge size
- Electropolished Stainless Steel case
- 316 Stainless Steel wetted parts
- Meets the requirements of 3-A
- C.I.P, S.I.P and Autoclave (only dry gauges are recommended for Autoclave)


	SPECIFICATIONS					
Pressure ranges	0 psig to 30 psig through 0 psig to 600 psig					
Accuracy	±2.5% full scale					
Temperatureranges	Media -40 °F to 300 °F (-40 °C to 150 °C) Ambient 25 °F to 140 °F (-4 °C to 60 °C) Storage 25 °F to 140 °F (-4 °C to 60 °C)					
Measuring element	316 Stainless Steel Bourdon tube					
Connection	3/4" Sanitary Clamp, 316L Stainless Steel Diaphragm 316L Stainless Steel, electropolished to 32 µin Ra or better					
Case	2" Electropolished 304 Stainless Steel					
Lens*	Polycarbonate					
Pointer	Balanced Aluminum, black finish					
Dial	Aluminum, white background, black print					
Movement	Stainless Steel					
Fill liquid	Glycerin, USP Grade					

^{*}Note: Autoclave requires the addition of optional laminated safety glass lens

Diaphragm seal must be installed facing downward or in a vertical position for drainability. Do not install diaphragm seal facing in an upward position.

ORDERING INFORMATION									
SERIES	100	10 Series fractional							
CLAMP SIZE	06	3/4"							
FILL LIQUID	1	Glycerin	Other	food grade quality fill fluids available – please consult factory					
GAUGE SIZE	20	2"							
PRESSURE RANGES	43	0 psig to 30 psig	55	0 psig to 160 psig	64	0 psig to 400 psig			
	46	0 psig to 60 psig	58	0 psig to 200 psig	70	0 psig to 600 psig			
	49	0 psig to 100 psig	61	0 psig to 300 psig					
OPTIONS	0	None	3	Safety Glass Lens (Required for Autoclave applications)					

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.



2" Gauge with 3/4" ASME-BPE Sanitary Clamp Connection



